

Integrated Suite of 12 Instruments for Interactive, Cost-Effective, Multidisciplinary, Hands-On Learning

NI ELVIS II **NEW!**

- Design and prototyping platform for circuit design, control, instrumentation, telecommunications, and embedded/MCU experiments
- Complete integration with Multisim for circuits and electronics
- Hi-Speed USB plug-and-play interface
- Virtual instrumentation suite includes oscilloscope, digital multimeter (DMM), function generator, variable power supply, Bode analyzer, arbitrary waveform generator, dynamic signal analyzer (DSA), voltage/current analyzer with LabVIEW source code
- Completely open and customizable in LabVIEW graphical system design environment
- Express VIs for point-and-click configuration of customized instruments in LabVIEW and LabVIEW SignalExpress

Workstation Features

- New, sleek design with an open connector architecture for third-party boards
- Isolated DMM for better signal integrity
- Short-circuit and high-voltage protection with resettable fuse board
- Variable power supplies – manual or programmatic control
- Function generator – manual or programmatic control
- ±15 and +5 V supply available



Overview

NI ELVIS, an educational design and prototyping platform based on NI LabVIEW graphical system design software, is a leading tool for teaching concepts in areas such as instrumentation, circuits, control, communication, and embedded design in a hands-on, interactive manner. It features a new design and an integrated suite of the 12 most commonly used instruments in a compact, rugged, laboratory-friendly form factor. NI ELVIS II includes a Hi-Speed USB interface that delivers a complete design and prototyping platform you can use from lower-division freshman classes to advanced senior classes to help students learn concepts from circuit design to telecommunications.

NI ELVIS II is a primary component of the NI electronics education platform along with NI Multisim, a leading tool for SPICE simulation and schematic capture in academia, and the NI LabVIEW graphical system design platform. Students can simulate theoretical concepts in Multisim, prototype the actual circuit with NI ELVIS II, and compare the simulation with real-world measurements using LabVIEW and LabVIEW SignalExpress. With NI ELVIS II and Multisim 10.1, learning circuits becomes more interactive using features such as 3D NI ELVIS II as well as the ability to access NI ELVIS II instruments inside the Multisim environment and switch from simulated data to real-world data with a single mouse click. For more information on the NI electronics education platform, visit ni.com/eep.

Features	NI ELVIS I	NI ELVIS II
12 integrated instruments	✓	✓
PCI/PCMCIA	✓	–
Integrated USB	–	✓
Isolated digital multimeter	–	✓
NI-DAQmx software	–	✓
True Multisim integration	–	✓

Table 1. NI ELVIS I versus NI ELVIS II




Figure 1. The NI ELVIS Education Platform

Integrated Suite of 12 Instruments for Interactive, Cost-Effective, Multidisciplinary, Hands-On Learning

LabVIEW Accessibility

NI ELVIS II is completely customizable in LabVIEW and includes Express VIs for each of the 12 instruments in its virtual instrumentation suite. This provides point-and-click configuration capabilities for the individual instruments, which makes building customizable instruments very easy. You also can use NI ELVIS II with LabVIEW SignalExpress to help students compare simulated data from Multisim and real-world data from NI ELVIS and create interactive reports for class assignments.




Figure 2. Integration with NI LabVIEW

Open Architecture with Plug-In Boards for Multidisciplinary Education

NI ELVIS II is an open architecture, which helps leading teaching solution providers take advantage of the platform. Plug-in boards for NI ELVIS II are available from the following companies:

- Control design with Quanser trainers
 - Quanser QNET DC motor
 - Quanser QNET inverted pendulum
 - Quanser QNET HVAC system




Figure 3. Quanser QNET plants and NI ELVIS II

- Embedded/MCU design with Freescale Microcontroller Student Learning Kit (SLK) featuring the following application modules:
 - 8-bit HCS08
 - 16-bit HCS12/HCS12X/DSP
 - 32-bit ColdFire processor
 - RF transceiver




Figure 4. Freescale Microcontroller SLK and NI ELVIS II

- Telecommunications with Emona DATEx telecommunications trainer for NI ELVIS



Figure 5. Emona DATEx Telecommunications Board and NI ELVIS II

Other Companion Products

- Circuits – Electronics education platform with Multisim
- Embedded/DSP – Analog Devices ADSP-BF537 Blackfin Processor
- Sensors – Vernier sensor adapters for NI ELVIS

Ordering Information

Bundles

NI ELVIS II Circuit Design Bundle.....	780379-01
<i>Includes NI ELVIS II, Multisim, LabVIEW, LabVIEW SignalExpress, and user manuals.</i>	
NI ELVIS II Basic Bundle	780378-01
<i>Includes NI ELVIS II workstation, NI ELVIS II prototyping board, NI LabVIEW (required), and user manuals.</i>	
NI ELVIS II instrumentation design and training platform....	780380-01
NI ELVIS II prototyping board	188432-01

BUY NOW!

For complete product specifications, pricing, and accessory information, call 800 813 3693 (U.S.) or go to ni.com/eep.

Integrated Suite of 12 Instruments for Interactive, Cost-Effective, Multidisciplinary, Hands-On Learning

Specifications

Performance is typical at 25 °C unless otherwise specified.

Analog Input

Channels.....	8 differential or 16 single-ended
ADC resolution.....	16 bits
Absolute accuracy.....	Refer to NI ELVIS II Specifications at ni.com/manuals
Maximum sampling rate.....	1.25 MS/s single channel, 1.00 MS/s multichannel (aggregate)
Input range.....	±10 V, ±5 V, ±2 V, ±1 V, ±0.5 V, ±0.2 V, ±0.1 V
Maximum working voltage for analog inputs (signal + common mode).....	±11 V of AIGND
CMRR (DC to 60 Hz).....	90 dB
Input impedance	
Device on – AI+ or AI- to AIGND ...	>10 GΩ 100 pF
Device off – AI+ or AI- to AIGND...	820 Ω
Input bias current.....	±100 pA
Crosstalk @100 kHz	
(adjacent channel)	-70 dB
(nonadjacent channel)	-80 dB
Small signal bandwidth (-3 dB)	1.2 MHz
Input FIFO size.....	4095 samples
Scan list memory	4095 entries
Data transfers	USB signal stream, programmed I/O
Overvoltage protection (AI±, AISENSE)	
Device on.....	±25 V for up to four lines
Device off.....	±15 V for up to four lines
Input current during overvoltage condition	±20 mA max per line

Analog Triggers

Number of triggers.....	1
Source	AI<0..15>, ScopeCH0, ScopeCH1
Functions	Start trigger, reference trigger, pause trigger, sample clock, convert clock, sample clock timebase
Source level	±Full scale
Resolution	10 bits
Modes	Analog edge triggering, analog edge triggering with hysteresis, and analog window triggering

Arbitrary Waveform Generator/Analog Output

Channels.....	2
DAC resolution.....	16 bits
Maximum update rate	
1 channel	2.8 MS/s
2 channels.....	2.0 MS/s
Timing resolution	50 ns
Output range	±10 V, ±5 V

Data transfer.....	USB signal stream, programmed I/O
AO waveform modes	Nonperiodic waveform, periodic waveform regeneration from onboard FIFO, periodic waveform regeneration from host buffer including dynamic update
Slew rate.....	20 V/μs

Digital I/O and PFI

Channels.....	24 DIO (Port 0), 15 PFI (ports 1 and 2)
Direction control	Each line individually programmable as input or output
Pull-down resistor	50 kΩ typ, 20 kΩ min
Input voltage protection.....	±20 V on up to two pins

PFI/Port 1/Port 2 Functionality

Functionality.....	Static digital input, static digital output, timing input, timing output
Debounce filter settings	125 ns, 6.425 μs, 2.56 ms, disable; high and low transitions; selectable per input

General-Purpose Counter/Timers

Counter/timers.....	2
Resolution	32 bits
Counter measurements.....	Edge counting, pulse, semiperiod, period, two-edge separation
Position measurements	X1, X2, X4 quadrature encoding with Channel Z reloading; two-pulse encoding
Output applications.....	Pulse, pulse train with dynamic updates, frequency division, equivalent time sampling
Internal base clocks	80, 20, 0.1 MHz
External base clock frequency	0 to 20 MHz
Base clock accuracy.....	50 ppm
Maximum frequency.....	1 MHz
Inputs.....	Gate, source, HW_Arm, Aux, A, B, Z, Up_Down

Frequency Generator

Channels.....	1
Base clocks	10 MHz, 100 kHz
Divisors.....	1 to 16
Maximum frequency	1 MHz
Base clock accuracy.....	50 ppm
Default output line.....	PFI 14/FREQ_OUT

External Digital Triggers

Source	TRIG BNC or any PFI
Polarity	Software-selectable for most signals

Integrated Suite of 12 Instruments for Interactive, Cost-Effective, Multidisciplinary, Hands-On Learning

Analog input function	Start trigger, reference trigger, pause trigger, sample clock, convert clock, sample clock timebase
Analog output function	Start trigger, pause trigger, sample clock, sample clock timebase
Counter/timer function	Gate, source, HW_Arm, Aux, A, B, Z, Up_Down

Digital Multimeter (DMM)

Isolated functions	DC voltage, AC voltage, DC current, AC current, resistance, diode
Isolation level	60 VDC/20 V _{rms} , Installation Category I
Resolution	5½ digits
Input impedance	11 MΩ
Input coupling	DC (DC voltage, DC current, resistance, diode) AC (AC voltage, AC current)
Nonisolated functions	Capacitance, inductance

Voltage Measurement

DC ranges	100 mV, 1 V, 10 V, 60 V
AC ranges	200 mV _{rms} , 2 V _{rms} , 20 V _{rms}
Accuracy	Refer to NI ELVIS II Specifications at ni.com/manuals
Input frequency range (AC mode)	40 Hz to 20 kHz

Current Measurement

DC range	2 A
AC ranges	500 mA _{rms} , 2 A _{rms}
Shunt resistor	0.1 Ω
Burden voltage	<0.6 V
Accuracy	Refer to NI ELVIS II Specifications at ni.com/manuals
Input frequency range (AC mode)	40 Hz to 5 kHz
Input protection	F 3.15 A 250 V, fast-acting user-replaceable fuse

Resistance Measurement

Ranges	100 Ω, 1 kΩ, 10 kΩ, 100 kΩ, 1 MΩ, 100 MΩ
Accuracy	Refer to NI ELVIS II Specifications at ni.com/manuals

Diode Measurement

Range	1 V
Nominal test current	1 mA (1 V range)

Capacitance Measurement

Range	50 pF to 500 uF
Accuracy	1%

Inductance Measurement

Range	100 μH to 100 mH
Accuracy	1%

Function Generator

Channels	1
Output waveform type	Sine, square, triangle
Frequency range	0.186 Hz to 5 MHz (sine) 0.186 Hz to 1 MHz (square and triangle)
Frequency resolution	0.186 Hz
Waveform amplitude range	10 V _{pp}
Waveform amplitude resolution	10 bits
Waveform amplitude accuracy	1% ±15 mV
Waveform offset range	±5 V
Duty cycle range	0 to 100%
Output impedance	50
Maximum output current	100 mA
Sine total harmonic distortion (THD) ..	-50 dB max @ 1 MHz
Sine flatness	-40 dB max @ 5 MHz -0.5 dB to 3 MHz-3 dB to 5 MHz

Modulation

Inputs	2 (AM and FM)
Modulation input range	±10 V
Amplitude modulation factor	10%/V
Frequency modulation factor	20%/V

Oscilloscope

Channels	2
Input coupling	AC or DC
Input impedance	1 MΩ 25 pF
Bandwidth (-3 dB)	1.7 MHz
DC accuracy	Refer to NI ELVIS II Specifications at ni.com/manuals

Dynamic Signal Analyzer

Accuracy	Refer to NI ELVIS II Specifications at ni.com/manuals
Frequency resolution	Software-controllable (200, 400, 800, 1600, 3200 Hz)

Bode Analyzer

Accuracy	Refer to NI ELVIS II Specifications at ni.com/manuals
Phase accuracy	1 Hz to 200 kHz

Two-Wire Current-Voltage Analyzer

Current range	±40 mA
Voltage sweep range	±10 V

Integrated Suite of 12 Instruments for Interactive, Cost-Effective, Multidisciplinary, Hands-On Learning

Three-Wire Current-Voltage Analyzer

Supported devices	NPN and PNP transistors
Minimum base current increment	0.48 μ A
Maximum collector current.....	\pm 40 mA
Maximum collector voltage	\pm 10 V

Impedance Analyzer

Measurement frequency range	1 Hz to 35 kHz
-----------------------------------	----------------

Power Supplies

+15 V Supply

Output voltage (no load)	+15 V \pm 5%
Maximum output current	500 mA
Short circuit protection	Resettable circuit breaker

-15 V Supply

Output voltage (no load)	-15 V \pm 5%
Maximum output current	500 mA
Short circuit protection	Resettable circuit breaker

+5 V Supply

Output voltage (no load)	+5 V \pm 5%
Maximum output current	2 A
Short circuit protection	Resettable circuit breaker

Positive Variable Supply

Output voltage	0 to +12 V
Voltage setpoint resolution	10 bits
Voltage accuracy (no load).....	100 mV
Maximum output current	500 mA
Short circuit protection	Self-resetting current limiter

Negative Variable Supply

Output voltage	0 to -12 V
Voltage setpoint resolution	10 bits
Voltage accuracy (no load).....	100 mV
Maximum output current	500 mA
Short circuit protection	Self-resetting current limiter

Calibration

Recommended warm-up time.....	15 minutes
Calibration Interval	1 year

Communication

Bus interface	Hi-Speed USB
USB signal stream	4 streams; can be used for analog input, analog output, and counter/timers

Physical

Dimensions.....	34.3 by 28.0 by 7.6 cm (14.5 by 11 by 3 in.)
Weight (with prototyping board)	1.9 kg (4.2 lb)

Environmental

Operating temperature	10 to 35 °C
Storage temperature.....	65 °C
Humidity	10 to 90% relative humidity, noncondensing
Maximum altitude.....	2000 m
Pollution degree (indoor use only).....	2

Safety and Compliance

Safety

This product is designed to meet the requirements of the following standards of safety for electrical equipment for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 61010-1, CSA 61010-1

Note: For UL and other safety certifications, refer to the product label or visit ni.com/certification, search by model number or product line, and click the appropriate link in the Certification column.

Electromagnetic Compatibility

This product is designed to meet the requirements of the following standards of EMC for electrical equipment for measurement, control, and laboratory use:

- EN 61326 EMC requirements; Minimum Immunity
- EN 55011 Emissions; Group 1, Class A
- CE, C-Tick, ICES, and FCC Part 15 Emissions; Class A

Note: For EMC compliance, operate this device according to product documentation.

CE Compliance

This product meets the essential requirements of applicable European Directives, as amended for CE marking, as follows:

- 2006/95/EC; Low-Voltage Directive (safety)
- 2004/108/EC; Electromagnetic Compatibility Directive (EMC)

Note: Refer to the Declaration of Conformity (DoC) for this product for any additional regulatory compliance information. To obtain the DoC for this product, visit ni.com/certification, search by model number or product line, and click the appropriate link in the Certification column.

Waste Electrical and Electronic Equipment (WEEE)

EU Customers: At the end of their life cycle, all products must be sent to a WEEE recycling center. For more information about WEEE recycling centers and National Instruments WEEE initiatives, visit ni.com/environment/weee.htm.

NI Services and Support



NI has the services and support to meet your needs around the globe and through the application life cycle – from planning and development through deployment and ongoing maintenance. We offer services and service levels to meet customer requirements in research, design, validation, and manufacturing. Visit ni.com/services.

Training and Certification

NI training is the fastest, most certain route to productivity with our products. NI training can shorten your learning curve, save development time, and reduce maintenance costs over the application life cycle. We schedule instructor-led courses in cities worldwide, or we can hold a course at your facility. We also offer a professional certification program that identifies individuals who have high levels of skill and knowledge on using NI products. Visit ni.com/training.

Professional Services

Our NI Professional Services team is composed of NI applications and systems engineers and a worldwide National Instruments Alliance Partner program of more than 600 independent consultants and

integrators. Services range from start-up assistance to turnkey system integration. Visit ni.com/alliance.



OEM Support

We offer design-in consulting and product integration assistance if you want to use our products for OEM applications. For information about special pricing and services for OEM customers, visit ni.com/oem.

Local Sales and Technical Support

In offices worldwide, our staff is local to the country, giving you access to engineers who speak your language. NI delivers industry-leading technical support through online knowledge bases, our applications engineers, and access to 14,000 measurement and automation professionals within NI Developer Exchange forums. Find immediate answers to your questions at ni.com/support.

We also offer service programs that provide automatic upgrades to your application development environment and higher levels of technical support. Visit ni.com/ssp.

Hardware Services

NI Factory Installation Services

NI Factory Installation Services (FIS) is the fastest and easiest way to use your PXI or PXI/SCXI combination systems right out of the box. Trained NI technicians install the software and hardware and configure the system to your specifications. NI extends the standard warranty by one year on hardware components (controllers, chassis, modules) purchased with FIS. To use FIS, simply configure your system online with ni.com/pxiadvisor.

Calibration Services

NI recognizes the need to maintain properly calibrated devices for high-accuracy measurements. We provide manual calibration procedures, services to recalibrate your products, and automated calibration software specifically designed for use by metrology laboratories. Visit ni.com/calibration.

Repair and Extended Warranty

NI provides complete repair services for our products. Express repair and advance replacement services are also available. We offer extended warranties to help you meet project life-cycle requirements. Visit ni.com/services.



ni.com • 800 813 3693

National Instruments • info@ni.com

